

Medical lightings

MEDICAL DEVICE CLASS 1 - CE CERTIFIED
ON/OFF SWITCH - LED LIFE SPAN: 50 000H min.



Power cable length : 3 meters
Telescopic trolley base INCLUDED (5 swivel Ø 53 mm wheels)
Adjustable from 600 to 1000 mm

→ LED Bella Lumax CE

Head dimensions: 160 x 130 mm
Flexible arm: 700 mm
Light intensity: 2300 Lumens
Colour of temperature: 4500°K (neutral white)
Electric consumption: 18 Watts

REF. 327.76

→ LED Hepta CE

Head dimensions: 110 x 100 mm
Flexible arm: 650 mm
Light intensity: 980 Lumens
Colour of temperature: 4500°K (neutral white)
Electric consumption: 7 Watts

REF. 327.77



→ LED Hydra CE

Head dimensions: 60 x 100 mm
Flexible arm: 1000 mm + 2 x 250 mm
Light intensity: 420 Lumens x 2
Colour of temperature: 4500°K (neutral white)
Electric consumption: 6.5 Watts

REF. 327.78

→ LED Lina CE

Head dimensions: 500 x 25 mm
Flexible arm: 650 mm
Light intensity: 1680 mm
Colour of temperature: 4500°K (neutral white)
Electric consumption: 13 Watts

REF. 327.79

→ ACCESSORIES

REF..

Universal clamp for rail or tube fixing

327.60



309.04

309.05

309.06

→ Negatoscopes CE

Moulded cord European norm
Epoxy metal cabinet and textured epoxy paint
Stainless steel film holder - Films hold by cadmia rollers
Opalin diffusion screen mounted on slide rail

MODEL	DIM. L X W X H	REF.
Horizontal - 1 range (2 x 15 W)	450 x 130 x 485 mm	309.04
Horizontal - 2 ranges (4 x 15 W)	810 x 130 x 485 mm	309.05
Horizontal - 3 ranges (2 x 40 W)	1226 x 130 x 485 mm	309.06
Horizontal - 4 ranges (2 x 65 W)	1526 x 130 x 485 mm	309.07
Vertical - 3 ranges (2 x 40 W)	450 x 130 x 1255 mm	309.08