



IBS GROUPC

Onex 102 Electro-Hydraulic Surgery Table



Onex 102

Electro-Hydraulic Surgery Table

The Onex 102 is an Electro-hydraulic operating surgery table that can be set up and positioned easily with a remote control. The interchangeable top is made of shape memory material to provide great comfort for the patient.

With it's highly stable hydraulic system, the table can be set up to make all kinds of surgical positions, precisely and quietly.

ACCESSORIES

- Headrest system
- Crossbar adaptor
- Arm/Hand surgery table
- Facial/Occopital head rest
- Orthopedic extension device
- Wrist support system
- X-ray cassette tray
- Body restraint strap
- Arm restraint strap
- Leg restraint strap

- L-shaped Anesthesia Screen
- L-shaped Anesthesia Screen with 2 wings
- Easy arm board
- Arm board with ball-joint
- Lateral Arm board
- Leg support padded
- Lateral support padded
- Shoulder Support padded
- Foot-rest padded





- External Kidney Elevator
- Radial Accessory clamp
- Accessory clamp
- Infusion Stand
- Instrument tray
- Drain pan











FEATURES

- Special design of low position
- Flexible and wide-angle adjusting can meet different requirements of surgical positions.
- 4-section design to meet different requirements of surgical positions
- Acentric structure with T-shape base. Convenient for using X-ray and C-arm
- Stable hydraulic system with square column, high load-bearing and low movement noise
- Detachable polyurethane pads, antipollution, anticorrosive and moisture-proof

- Wire handset control with touch keypad, safety lock in 30 seconds to prevent faulty operation
- Fast and solid assembling and disassembling with high quality pneumatic spring
- Stainless steel body structure
- Backup battery supply (optional)

TECHNICAL SPECIFICATIONS SternMed Electro-Hydraulic Surgery Table	Onex 102 (standard position type)	Onex 102 (low position type)
Control of Position	Electro hydraulic with a wire handset	
Max. Table Length (Inc. Head Plate & Leg Plates)	2050mm	2050mm
Max. Table Width W/O side rails	500mm	500mm
Lowest Table Level	690mm	550mm
Highest Table Level	1040mm	800mm
Lifting Distance	350mm	250mm
Trendelenburg/Reverse	25°/25°	20°/15°
Lateral Tilt (left/right)	20°/20°	20°/20°
Max. Height of Cone	110mm	110mm
Head Plate (up/down)	90°/90°	90°/90°
Back Plate (up/down)	75°/12°	75°/12°
Leg Plate (down/split)	10°/100°/100° x 2	10°/100°/100° x 2
Flex/Reflex	192°/100°	192°/100°
Load Capacity	200kg	200kg
Power Supply	A.C. 220V+10%/50+1Hz	-
Input Power	<650VA	





