

Auto projector Chart Projector

감각적인 디자인의 차세대 차트프로젝터



Specifications

Charts	42EA	Dimensions	Main Body (Stand 제외) : 202(W)×364(D)×172(H) mm		
Distance of projection	2.5 ~ 8m		Main Body (Stand 제외) : 202(W)×364(D)×240(H) mm		
Chart magnification	30 imes (when projected at 5m distance)		Remote Controller : 64(W)×196(D)×20(H) mm		
Lamp	PACP-7000 : Halogen lamp (6V-20W)	Weights	PACP-7000 (Stand 제외) : 4.9 kg		
	PACP-7000L : LED lamp		PACP-7000L (Stand 제외) : 4.7 kg		
Masks	35EA (1 open mask, 5 horizontal line maksks, 8 vertical line		Remote Controller : 160 g (Battery included)		
	masks, 21 single letter masks)	Basic Accessories	Product Body(PACP-7000 or PACP-7000L), Screen		
Filter	1 Red/Green Filter		Remoto Controller, Table Stand, Dust Cover, Power Cable		
Chart rotation speed	average 0.21 sec (min. 0.092sec, max.0.324sec)		T wrench, Fuse, Lamp(PACP-7000), Battery		
Power supply	AC100-240V, 50/60Hz	Optional accessories	Red/Green glasses, Polarization glasses		
Power consumption	PACP-7000 : 100VA				
	PACP-7000L : 60VA				

디자인과 사양은 사전에 예고없이 변경될 수 있습니다.



대전광역시 동구 삼성동 292-4 (우)300-812 Tel 042-632-3536 Fax 042-632-3537 WWW.POTEC.BIZ webmaster@potec.biz

Distributed by

Next generation Chart Projector PACP-7000/PACP-7000L will satisfy you with its swift and accurate optometry system.

CHART TYPE



	D TYPE
259* 50022 ** 20000 ** 66022 ** *** *** *** 368* 20000 ** 20000 ** 66022 ** *** *** *** ***	
ARE® POZ® REMOVA 9 NOPOV9 NOPOV9 REMOVA 9 NOPOV9 REMOVA 9 NOPOV9 REMOVA 9 NOPOV9 REMOVA 9 NOPOV9 REMOVA 9 NOPOV9 REMOVA 9 NOPOV9 REMOV9	-
	PACP7000(L) REMOTE CONTROLLER RC-0

C TYPE ★ 200 0 ~ 0 100 ▲ ★ ₩ 50 ▲ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ₩ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ ★ 50 ★ ★ ★ 50 ★ ★ ★ 50 ★ ★ ★ 50 ★ ★ ★ 50 ★ ★ ★ 50 ★ 50 ★ 50 ★ 50 ★ 50 ★ ★ 50 ★ 50 ★ 50 ★ 50 ★ 50 ★ 50 ★ 50 ★ 50 29360 62830 83692 •
 259:00
 86692:00
 28966:0
 66982:0
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1</t
 ARE
 LTHDV100 RNEFP 10
 RREFP 10 KNTDL 00
 RZNFD 10 ALTOF 20
 TKAL0 20 ALTOF 20
 AOFTL 10 ORPOA 10

 KEOVA 30
 KOPDV 30
 COPLA 20
 COPLA 20
 COPLA 20
B 0 0 B 30 83 700 092 C 480 C 490 C 490

							F	R TYPE
X at	•-••= • • • •= • • • •=	040¥*0.4 0¥0**0.5 4¥*80.6	•~¥4007 •¥4~•08 4•¥•408	29360 62830 83692		:		POTEC CHART PROJECTOR
	EWBEROJ BERWEOA RWBEROS		MUSEM 1.0 ESEWS 1.2 SMUSE 1.5	\bigcirc				
259°1 368°3	62483°3 28956°4 85632°5	95826 ^{0.6} 26395 ^{0.7} 58942 ^{0.6}	56382°* 462981° 8352912	••	""	+		
БЪЛ« ФЮП«	ОРИЪГ 0.2 ФЛПХТ 0.3 ЯЪШЬЮ 0.4						$\left(+\right)$	
C •••		COOUC 0.2 CCOCO 0.3 CUCOC 0.4	COORC 0.5 OCRODO 0.8 UORCC 0.7	0000000 0000000 00000000 0000000	0966012 0066015 0000620		$\begin{tabular}{ c c c c c } \hline \hline \end{tabular}$	PACP-7000(L) REMOTE CONTROLLER RC-R



Free voltage & Free frequency

By applying SMPS, it can show a steady chart brightness that is not almost affected by the changes of AC voltage input.

Body channel is operated by remote control

Body channel was operated on the previous product through the switch of the body. But body channel can be easily operated on the new product only by the remote control.

Clear & various charts

It shows clear 42 charts, including eyesight, astigmatic angle, binocular vision, heterophoria, stereopsis and so on, and the mask(vertical, horizontal, single).

Rapid chart change speed

We can provide rapid and comfortable optometry service to the customers with the chart change speed of the industry top level.

Refined & outstanding design

The refined appearance, which shows LED lighting at the side of the product, will upgrade the optometry room.

PACP-7000L

High luminance LED can provide a clearer chart than halogen lamp and reduces the maintenance effort.

The next generation chart projector with its outstanding design. PACP-7000/PACP-7000L

